


**NOTES:**

1. THE FINAL LOCATIONS (AND LENGTH) OF THE TEMPORARY NOISE BARRIERS SHALL BE PROPOSED BY THE CONTRACTOR DEPENDING ON THE SITE CONDITION AND EXTEND OF WORKS. IT SHALL BE REVIEWED AND VERIFIED BY THE ENGINEER AND ENVIRONMENTAL TEAM LEADER TO ENSURE ITS EFFECTIVENESS. TEMPORARY ACCESS SHALL BE PROVIDED FOR PEDESTRIAN AND VEHICULAR TRAFFIC.

**LEGEND:**

 MINIMUM 3m TALL PURPOSED BUILT SITE HOARDING BARRIER TO SCREEN THE DIRECT LINE OF SIGHT TO THE NSRs

45m(length)

YUEN LONG, KAM TIN,  
NGAU TAM MEI AND TIN SHUI WAI  
DRAINAGE IMPROVEMENT, STAGE1, PHASE 2B

Title :

**LOCATIONS OF PROPOSED  
TEMPORARY NOISE BARRIERS**

  
**BLACK & VEATCH HONG KONG LIMITED**  
博威工程顧問有限公司

Figure No. 5.3	Revision 0
Reference -	File Name 3820470201-106.DGN
Prepared* MC	Checked KIL
Date MAY, 2006	Scale 1 : 2500